

Tactile Carpet Kit System – Specifications

Dimensions

300mm x 300mm x 3mm

Composition

State of the art thermoplastic polyurethane indicators and a re-constituted nylon base pad.

Types

Hazard profile only.

Slip resistance

Pathfinder Tactile Indicators provide excellent slip resistance and have been tested to AS/NZS 4586:1999 by the CSIRO, test number 2020sa achieving an R11 rating.

Chemical resistance

Pathfinder Tactile Indicators are resistant to most common acids, alkalis, oils and greases.

Installation

Must be in accordance with PFSA installation instructions. Pathfinder Tactile Carpet Kit are suitable for internal and external applications.

Australian standards

Pathfinder Tactile Indicators have a 45 luminance contrast as per AS1428.4 2002, they also conform to the slip resistance requirements for pedestrian surfaces as stated under the AS/NZS 4586:1999.

Warranty

PFSA warrants all their products within the terms of PFSA standard warranty, against specific suitable installations when installed correctly as per PFSA installation procedure.

Consult your distributor / installer for any specific test reports if required.

Features & benefits

- Most aesthetically pleasing indicator system on the market
- Conforms to AS1428.4 2002
- Large range of high luminance colours (45 as required by standards)
- Can be installed with any carpet types
- Customised colour service available
- Extremely hard wearing and durable
- Suitable for internal or external use
- UV stable
- Easy to install by carpet layer or trades person
- Extremely hard to accidentally remove
- Slip resistant as required by AS/NZS 4586:1999

colour range

